

YU DRAIN SYSTEM (FastDrain 75 Endcap Inspection with Outlet)



PRODUCTFILE 202013-04 (01)

YUCON SOLUTIONS bvba
Fraterstraat 109a
9820 MERELBEKE
BELGIUM

info@about-yu.com
order@about-yu.com
www.about-yu.com

BE 0508 855 070

We also offer a number of polymer end sections within our YU.Drain FastDrain 75 product range.

In a default configuration, an inspection hatch should be provided at either end of the conduit for maintenance purposes. The package is containing a left-hand and right-hand conduit connector

But If this inspection hatch is installed at the end of the conduit construction, as provided by default, an end-piece must be foreseen for this.

This version of the end-piece has a run-off with an outside diameter of 46.9mm. This makes it possible to have a side drain outlet in combination with a standard inspection hatch.

MATERIAL PROPERTIES

Material:	PE – Polyethylene (C ₂ H ₂) _n
Density:	0,91-0,96 g/cm ³
Height:	61,5 mm
Width:	104,2 mm
Outer diameter:	46,9 mm

WARRANTY PROVISION

If a component fails to operate correctly or should become faulty under normal use and within a period of one year from its date of installation, said component shall be repaired or replaced free of charge.

The following shall be excluded from this warranty provision:

- ▶ Improper application
- ▶ Transport damage
- ▶ Improper assembly
- ▶ Infringements of component and/or maintenance instructions.